

MH-Shear Series



Standard Equipments

- NC control
- Programmable motorized backgauge with 750 mm travel
- 1 pc. squaring arm with scale
- 2 pcs. sheet support arm
- Finger protection
- Ball transfer table
- Cutting line lighting with shadow line
- Easy blade gap adjustment from front
- Ball screw
- Cut counter
- Portable foot control with emergency stop button
- Photocell on the back safety guards



Type	Cutting angle	Cutting Length	Capacity (St 42)	Length	Width	Height	Table Width	Table Height	Main Motor	Backgauge Motor	Backgauge range	Cutting stroke	Weight
	(°)	mm	mm	mm	mm	mm	mm	mm	kW	kW	mm	1/min	kg
MH-SHEAR 1106	2°	1100	6	1750	2250	1400	455	800	7,5	0,55	750	31	2000
MH-SHEAR 1406	2°	1400	6	2050	2250	1400	455	800	7,5	0,55	750	31	2300
MH-SHEAR 1505	2°	1560	5	2250	2250	1400	455	800	7,5	0,55	750	31	2500
MH-SHEAR 2004	1,30°	2060	4	2600	2250	1400	455	800	7,5	0,55	750	31	3000
MH-SHEAR 2504	1,30°	2560	4	3100	2250	1400	455	800	7,5	0,55	750	31	3500
MH-SHEAR 3004	1,30°	3060	4	3600	2250	1400	455	800	11	0,55	750	31	4000